

CON-SMPS

DC-DC CONVERTER



POSITIVE PROBLEM SOLVING **+ =**

The CON-SMPS range of switch-mode DC-DC Converters provides maximum output powers of 75 watts to 750 watts. The range switches at 100 kHz and achieves efficiencies of 88%.

This high efficiency translates into a very compact package and a lower level of input energy to power your application. The units incorporate a passive power factor correction circuit and all components are derated to provide long term reliability and trouble free use. All units in the series are fully enclosed and have mounting options on either the base or side of the case.

- + Overload & Over Temperature Protection
- + Other O/P Voltages on Request
- + CC & CV Operating Modes
- + High Efficiency up to 88%
- + Rugged Design
- + PFC Circuit

FURTHER DETAILS

The output characteristics are CC /CV and with over temperature, overload protection elevated operating temperature (70°C) and a conformal protection option these power supplies are suitable for a wide range of applications.

The power platforms in this range have formed the base of many customer specific requirements in a variety of industry sectors including: industrial control systems, military systems, submersible vehicles plus many more.

SELECTION TABLE

Part Number	Max. Power	Voltage Range	Current	Dimensions	Weight
CON-SMPS 75-5-DCx	75W	5V	15A	140 × 100 × 42mm	1.2kg
CON-SMPS 75-12-DCx	75W	12 - 15V	5A	140 × 100 × 42mm	1.2kg
CON-SMPS 75-24-DCx	75W	24 - 28V	3A	140 × 100 × 42mm	1.2kg
CON-SMPS 75-48-DCx	75W	48 - 60V	1.5A	140 × 100 × 42mm	1.2kg
CON-SMPS 150-5-DCx	150W	5V	30A	200 × 100 × 42mm	1.5kg
CON-SMPS 150-12-DCx	150W	12 - 15V	12A	200 × 100 × 42mm	1.5kg
CON-SMPS 150-24-DCx	150W	24 - 28V	5A	200 × 100 × 42mm	1.5kg
CON-SMPS 150-48-DCx	150W	48 - 60V	3.3A	200 × 100 × 42mm	1.5kg
CON-SMPS 250-5-DCx	250W	5V	50A	225 × 127 × 48mm	2.1kg
CON-SMPS 250-12-DCx	250W	12 - 15V	20A	225 × 127 × 48mm	2.1kg
CON-SMPS 250-24-DCx	250W	24 - 28V	12A	225 × 127 × 48mm	2.1kg
CON-SMPS 250-48-DCx	250W	48 - 60V	6A	225 × 127 × 48mm	2.1kg
CON-SMPS 350-5-DCx	350W	5V	60A	225 × 127 × 48mm	2.4kg
CON-SMPS 350-12-DCx	350W	12 - 15V	25A	225 × 127 × 48mm	2.4kg
CON-SMPS 350-24-DCx	350W	24 - 28V	15A	225 × 127 × 48mm	2.4kg
CON-SMPS 350-48-DCx	350W	48 - 60V	7.5A	225 × 127 × 48mm	2.4kg
CON-SMPS 500-12-DCx	500W	12 - 15V	33A	227 × 127 × 63mm	2.9kg
CON-SMPS 500-24-DCx	500W	24 - 28V	19A	227 × 127 × 63mm	2.9kg
CON-SMPS 500-48-DCx	500W	48 - 60V	9A	227 × 127 × 63mm	2.9kg
CON-SMPS 500-90-DCx	500W	90 - 110V	5A	227 × 127 × 63mm	2.9kg
CON-SMPS 500-125-DCx	500W	125 - 150V	3.5A	227 × 127 × 63mm	2.9kg
CON-SMPS 750-12-DCx	750W	12 - 15V	50A	227 × 127 × 63mm	2.9kg
CON-SMPS 750-24-DCx	750W	24 - 28V	30A	227 × 127 × 63mm	2.9kg
CON-SMPS 750-48-DCx	750W	48 - 60V	15A	227 × 127 × 63mm	2.9kg
CON-SMPS 750-90-DCx	750W	90 - 110V	7A	227 × 127 × 63mm	2.9kg
CON-SMPS 750-125-DCx	750W	125 - 150V	5A	227 × 127 × 63mm	2.9kg

Replace DCx with input range required.

Different output ranges and application/user specific options are possible. Please contact ETPS Ltd to discuss your requirements.

TECHNICAL DATA

GENERAL	
DC Input	See option table
Safety	EN 60950
Creeping and clearance	8/8
Emission	EN 61000-6-4
Immunity	EN 61000-6-2
Protection class	1
Operating temperature	0 - 70°C
Temperature coefficient	0.02%/°C
Storage temperature	-45 to 85°C
Derating from 55°C	-2.5%/°C
MTBF MIL Handbook	120.000h
Load regulation	0.2% [10 - 90 - 10% load]
Input regulation	0.1% [± 15%]
Response time	800µsec [20 - 100 / 100 - 20%]
Ripple & noise	0.2% / 1% [rms/pp]
Output adjustable	± 5%
Remote sense	+0.3V [typ]

OPTIONS

CODE	DESCRIPTION
/DC1	12Vdc nominal voltage [9-18Vdc range] 60% of max power available
/DC2	24Vdc nominal voltage [18-36Vdc range] 80% of max power available
/DC3	48 / 60Vdc nominal voltage [36-72Vdc range] 90% of max power available
/DC4	110Vdc nominal voltage [88-140Vdc range] 100% of max power available
/DC5	220Vdc nominal voltage [176-275Vdc range] 100% of max power available
/AI-5CC	0-5V = 0 to I_{MAX} [setting only, no readback]
/AI-5CV	0-5V = 5V to V_{MAX} [for 5V units range is 2V to V_{MAX}] [setting only, no readback]
/AI-5CC/CV	0-5V = 0 to I_{MAX} , 5V to V_{MAX} [for 5V units range 0 to I_{MAX} and 2V to V_{MAX}] [setting only, no readback]
/AI-10CC	0-10V = 0 to I_{MAX} [setting only, no readback]
/AI-10CV	0-10V = 5V to V_{MAX} [for 5V units range is 2V to V_{MAX}] [setting only, no readback]
/AI-10CC/CV	0-10V = 0 to I_{MAX} , 5V to V_{MAX} [for 5V units range 0 to I_{MAX} and 2V to V_{MAX}] [setting only, no readback]
/LT	-20° to +70°C temperature range
/LT40	-40° to +70°C temperature range
/PF	AC power fail signal TTL or open collector
/L3	DC output power fail signal
/CC	Conformal coating
/IEC	IEC Inlet fitted [500W to 750W only]
/N+1	Blocking diode fitted [500W to 750W only]
/PS	Active power sharing input [500W to 750W only]
/AS	Auto select 90-264Vac [for 75W & 150W units]

Every effort is made to ensure that the information provided within this technical summary is accurate. However, ETPS Ltd must reserve the right to make changes to the published specifications without prior notice. Where certain operating parameters are critical for your application we advise that they be confirmed at the time of order. ETPS Ltd specialises in modifying its proven platforms to suit your needs. Please contact our office if your requirement is non-standard. Please note that your actual unit may differ from those shown.



“
WE ARE
POSITIVE
PEOPLE
”

ETPS engineer electronic power supply and testing systems. Our problem solving skills provide the spark of innovation to some of the world's leading technology brands.



Tel: +44 (0) 1246 452909
Sales: 0800 612 95 75
sales@etps.co.uk
www.etps.co.uk

ETPS Ltd
Unit 14, The Bridge
Beresford Way, Chesterfield
S41 9FG



POSITIVE PROBLEM SOLVING